

LED B5 T3 3U

Barcode: 8433325176129



Specification

| | |
|------------|------------|
| Dimension | D42*H163mm |
| Lampholder | E27 |
| Technology | LED |

Technical parameters

| | |
|-----------------------------------|-------------|
| Voltage | 220-240V ~ |
| Luminous flux | 1180lm |
| EEL | F |
| Current | 90mA |
| CRI | Ra≥80 |
| Beam angle | 360° |
| Hg% | Zero |
| Power | 12W |
| Incandescent Lamp Power | 82W |
| Frequency | 50/60Hz |
| Color temperature | 3000K |
| Power consumption per 1,000 hours | 12kwh/1000h |

Application environment

| | |
|---------------------|--------------|
| Environment | Indoor |
| Working Temperature | -10°C ~ 40°C |

Life span

| | |
|---------------------|-----------|
| Life span | 15000h |
| Switching frequency | 7500times |

Material

| | |
|----------------|---------------|
| Main Materials | Glass&Plastic |
|----------------|---------------|

Certification

| | |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Certification |   |
|---------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|

Package

| | |
|--------------------|-----------------|
| Package | pc/blister card |
| Outer Package | pcs/ctn |
| M.Package | pcs/shrink bag |
| Unit package qty | One |
| Middle package qty | Five |
| Outer package qty | Fifty |

Certification Download

Instruction
manual

Download