



L480300940

LED PLS 2G7 4 pin Glas T37x146mm 230V
620Lm 4.5W (PLS9W) 4000K 840 AC
Opaal Niet-Dimbaar

Marine & Industrie, PLS 2G7 4pin



| General | | Energy | | |
|-----------------------------|-------------|-------------------------|----------------|----------------|
| Eprel registration no | 2039289 | Operating voltage | 230 V | |
| Socket | 2G7 | Volt | 220..240 V | |
| Bulb shape | T37 | Frequency | 50..60 Hz | |
| Width | 37.00 mm | Watt | 4.5 W | |
| Depth | 21.00 mm | Current type | AC | |
| Height | 146.00 mm | Power factor | 0.9 | |
| Finish | Opal | Energy efficiency class | D | |
| Colour | White | Energy consumption | 5 W | |
| Colour housing | White | Lamp efficacy | 137.78 | |
| Body material | Glass | LED | | |
| Lifespan | 30000 hours | Filament LED | No | |
| Switches | 15000 | LED type | SMD 2835 | |
| Beam angle | 270 ° | Dimm type | Non-Dim | |
| Dimmable | No | Number of leds / sticks | 36 | |
| Degree of protection | IP20 | Colour consistency SDCM | SDCM6 | |
| Net weight | 0.033 kg | Dim to warm | No | |
| Warranty | 2 years | Adjustable beam angle | No | |
| Light | | Ordering details | | |
| Kelvin | 4000 K | L480300940 | Quantity pc(s) | EAN |
| Colour temp nr | 840 | Single package | 1 | 8718739071841 |
| Stable lumen | 620 lm | Inner carton | 10 | 18718739071848 |
| Color Rendering Index (CRI) | 80 | Outer carton | 100 | 28718739071845 |

