

# SLI033037CCT\_PW

SLI033037CCT\_PW



Power	<b>8 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>800 lm (360°)</b>	Colour temperature	<b>2700/4000/6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>25 °</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data


---

Code	SLI033037CCT_PW
Power	8 W
Nominal current	68 mA
Voltage	230 V
Energy consumption	8 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0,5
Useful luminous flux*	800 lm (360°)
Luminous flux**	600 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	3000 cd
Colour temperature	2700/4000/6000 K
Colour of light	CCT
Beam angle	25 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	17000 h
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	54x109x160 mm
For use	Inside/Outside
Assembly method	on track
Application	Inside
Made in	PRC
Other	Light color change function 2700K/4000K/6000K ,


## Related documents

---



 User manual



 Declaration of Conformity